



DSL-4030 SERIES

3-FUNCTION REAR LED LAMP



PRODUCT BENEFITS

- Attractive EU design with Dynamic Indicator
- Tail light that stands out due to Glowing Body technology
- IP69K Protection
- Multi-voltage 10-30V
- Available in Smoked or Clear lens

FUNCTIONS LAYOUT

Stop / Tail Function

Dynamic Direction Indicator Function



CONNECTION AND MOUNTING



300mm Cable Connection



DT Connection



Surface Mounting



Bolt Mounting

TECHNICAL SPECIFICATIONS

TECHNICAL DATA

Product Number		DSL-4030		
Operating Voltage		10V - 30V		
Reverse Polarity Protection		Yes		
Light Function		Stop / Tail	Direction Indicator	
Emitted Color		Red	Amber	
Material	Lens	PMMA		
	Housing	ABS		
Type of Mounting		Surface Mounting or Bolt Mounting		
Consumption		4W (Stop)	0.5W (Tail)	4,6W
Temperature Range		-40°C / +65°C		
Type of Protection		IP69K		
Approvals	ECE	R148	R148	
		R1 - S1	2a	
	EMC	10R-06 (CISPR 25 - Class 3)		
Type of Connection		300mm Cable or DT Connector		

CODES SERIES OVERVIEW

Variants Ref. No.	Smoked Lens	Clear Lens	Surface Mounting	Bolt Mounting	300mm Cable	DT Connector
DSL-4030	•		•		•	
DSL-4030DT	•		•			•
DSL-4030B	•			•	•	
DSL-4030BDT	•			•		•
DSL-4035		•	•		•	
DSL-4035DT		•	•			•
DSL-4035B		•		•	•	
DSL-4035BDT		•		•		•

DIMENSIONAL DRAWINGS

