OSRAM XENARC COOL BLUE INTENSE D3S

Extra-blue xenon light





Xenon extra blue

Extra blue light due to a special filling system used instead of conventional coating



Up to 6,000 Kelvin

High contrast and brilliantly blue light for most stylish and modern look on the road



Up to 20% more light

For better visibility and shorter reaction times compared to standard xenon lamps



The extra-blue xenon light with up to 6,000 K

XENARC COOL BLUE INTENSE - discover that modern look at high power! With its extra blue, high-contrast xenon light, this automotive lamp appeals especially to customers who like the perfect combination of stylish and individual design with exceptional road illumination. The high-tech xenon light with color temperatures of up to 6,000 Kelvin comes up with a highly efficient technology, brilliant effect and no-compromise design. Thanks to a special filling system which is used instead of conventional coating the lamp emits its extra blue light. This stylish light creates a high-attention effect that helps you to be better seen by other motorists. Discover the exceptionally bright, high-contrast and brilliantly blue light with up to 6,000 Kelvin and 20% more light! With XENARC COOL BLUE INTENSE, the night turns into day. Please note: XENARC lamp change is recommended to be carried out by a professional.

Technical data


Electrical data


| Power input | 35 W |
|-----------------------|---------|
| Nominal voltage | 42.0 V |
| Nominal wattage | 35.00 W |
| Test voltage | 13.5 V |
| Power input tolerance | ±3 % |

Photometrical data

| Luminous flux | 3200 lm |
|-------------------------|---------|
| Luminous flux tolerance | ±15 % |

Dimensions & weight





| Diameter | 9 mm |
|----------------|---------|
| Product weight | 63.00 g |
| Length | 80.0 mm |

Lifespan

| Lifespan B3 | 2000 h |
|-------------|--------|
| Lifespan Tc | 3000 h |

Additional product data

| Base (standard designation) | PK32d-5 |
|-----------------------------|---------|
| Capabilities | |
| Technology | HID |
| | |

Certificates & standards

| ECE category | D3S ¹⁾ |
|---------------------------|-------------------|
| Approval marks – approval | E1 approval |

1) To be operated only with approved electronic control gear

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------------------|---------------------------------|---|----------------------|--------------|
| 4052899148710 | XENARC COOL BLUE INTENSE D3S | Folding carton box 1 | 53 mm x 46 mm x 93 mm | 0.23 dm³ | 82.96 g |
| 4052899344501 | XENARC COOL BLUE INTENSE D3S | Shipping carton box 4 | 115 mm x 101 mm x 103 mm | 1.20 dm ³ | 357.00 g |
| 4052899344518 | XENARC COOL BLUE INTENSE D3S | Shipping carton box 48 | - x - x - | | |
| 4052899431768 | XENARC COOL BLUE INTENSE D3S | Hard Cover Box 2 | 114 mm x 48 mm x 106 mm | 0.58 dm ³ | 218.08 g |
| 4052899431775 | XENARC COOL BLUE INTENSE D3S | Shipping carton box 10 | 257 mm x 129 mm x 121 mm | 4.01 dm³ | 1170.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Download Data

| File |
|---|
| 360 Degree Image XENARC COOL BLUE INTENSE D3S 66340CBI |

Safety advice

XENARC lamp change is recommended to be carried out by a professional.

Legal advice

ECE approval

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.











Product datasheet | XENARC COOL BLUE INTENSE © 2020, OSRAM GmbH. All rights reserved.

